

F.P.H. Art Metal Sp.j.

Ul. Jabłoniowa 124, 83-331 Łapino Kartuskie, Poland Tel. 0048 58 681 80 78, Fax: 0048 58 681 80 64 www.art-metal.pl e-mail: biuro@art-metal.pl

Construction:


The fixture includes a threaded base (1) to which a tray (9) with an igniter module (2) and a lampholder (3) are attached. The igniter is normally hidden under a protective cover fitted to the tray. A RASTER (ODB-3) reflector (5) can be used optionally. A bulb (6) is fitted into the holder (3). A threaded shade (7) is slid over the fixture and screwed into the female threaded base. The connection is made tight by using a gasket (8).

Mounting instructions:

- *) -Attach the igniter module (2) and the holder (3) to the base.
- -lead the electrical cables out of the arm and place them neatly inside the fixture,
- -connect them to the igniter (2).
- -Fix the cover (4) in position.
- -Attach the arm to the base (1).
- -Put the bulb (6) in position.
- -Attach a RASTER reflector(5)
- -Position the gasket (8) in place and screw the shade (7) all the way in.

If any lantern elements are supplied factory-mounted, the mounting stages marked with *) should be omitted (as this has already been done by the manufacturer)

TECHNICAL DATA:



Power: ~230/50Hz

Protective class: I ()

IP65 -electrical part

IP65 -optical part










6

8




4


3



1.Incadescent bulb







Туре	Light-producing element	Lamp holder	Weight [kg]	Pn [W]	
				IC	EB
A5MH-70W	MH/HSI/HPI	E27	3,7	81	78
A5MH-100W	MH/HSI/HPI	E27	4,2	114	109
A5S-70W	WLS/SHP/SON	E27	3,7	81	78
A5S-100W	WLS/SHP/SON	E40	4,3	114	109
A5Z-E/Z	Bulb / MINI - LINX	E27	2,2	Max. 60	

Luminary dimensions I ØD Wind area H/D $A = 0.13m^2$ 420/350

WARNING!! The weight of the unit may slightly differ for individual production batches.







