



F.P.H. Art Metal Sp.j.

Ul. Jabłoniowa 124, 83-331 Łapino Kartuskie, Poland

Tel. 0048 58 681 80 78, Fax: 0048 58 681 80 64

www.art-metal.pl e-mail: biuro@art-metal.pl

art metal

POLE DPB - Catalogue card

Construction:

1. DPb pole base - cast aluminum.
2. Fastening disk - steel.
3. Steel pipe $\varnothing 133$.
4. Steel pipe $\varnothing 101$.
5. Steel pipe $\varnothing 88,9$.
6. Steel pipe $\varnothing 76,1$.
7. Masking frame - cast aluminum.
8. Inspection door.
9. Grounding bolt.

General information:

Pole	Standard height	Top diameter	Foundation	Maximum weight
DPb	< 6500 mm	$\varnothing 76$	F100	85 kg
DPb	7000 mm	$\varnothing 76$	F120	94 kg

The top of the pole depends on a luminary or a head.

Maximum height of the lantern - 9,0 m.

Pole finish:

- galvanizing of steel elements according to PN-EN ISO 1461
- wet, multilayer coating according to PN-EN ISO 8501-1
- standard colour RAL7021, RAL 9005, all other RAL palette colours as an option

Load capacity:

- maximum wind area for a standard pole: 0,7 m²
- capacity for the wind area I (V = 22 m/s), II terrain category, according to PN - EN 40-3-1, PN - EN 40-3-3



Pole fastening:

